## **EUROPEAN PATENT OFFICE**

### atent Abstracts of Japan

P42510 WO Leuchte

**PUBLICATION NUMBER** 

2003089880

PUBLICATION DATE

28-03-03

**APPLICATION DATE** 

14-09-01

APPLICATION NUMBER

2001279781

APPLICANT: GANTAN BEAUTY IND CO LTD;

INVENTOR: TAMANOI HIDEO;

INT.CL.

C23C 22/52

TITLE

PATINA COLOR EMITTING COMPOSITION LIQUID AND PATINA FORMING METHOD

ABSTRACT :

PROBLEM TO BE SOLVED: To provide a patina color emitting composition liquid which acceleratively forms patina on copper or a base material formed by dispersing and solidifying the copper or a base material formed with a copper oxidized film and a patina forming method.

SOLUTION: The patina color emitting composition liquid prepared by compounding cupric chloride and sodium carbonate with an aqueous solution of one or ≥2 kinds selected from sodium chloride, aluminum chloride, zinc chloride and tin chloride and this liquid is applied onto the copper or the base material formed by dispersing and solidifying the copper or the base material formed with the copper oxidized film and is subjected to brushing, by which the composite type artificial patina of the basic cupric chloride and the basic copper carbonate is formed.

COPYRIGHT: (C)2003,JPO





#### PATENT ABSTRACTS OF JAPAN

(11) Publication number: 2003089880 A

(43) Date of publication of application: 28.03.03

(51) Int. CI

C23C 22/52

(21) Application number: 2001279781

(22) Date of filing: 14.09.01

(71) Applicant:

**GANTAN BEAUTY IND CO LTD** 

(72) Inventor:

FUNAKI GANTAN YANAGIMACHI KOJI TAMANOI HIDEO

# (54) PATINA COLOR EMITTING COMPOSITION LIQUID AND PATINA FORMING METHOD

#### (57) Abstract:

PROBLEM TO BE SOLVED: To provide a patina color emitting composition liquid which acceleratively forms patina on copper or a base material formed by dispersing and solidifying the copper or a base material formed with a copper oxidized film and a patina forming method.

SOLUTION: The patina color emitting composition liquid prepared by compounding cupric chloride and sodium

carbonate with an aqueous solution of one or  $_{\Xi}2$  kinds selected from sodium chloride, aluminum chloride, zinc chloride and tin chloride and this liquid is applied onto the copper or the base material formed by dispersing and solidifying the copper or the base material formed with the copper oxidized film and is subjected to brushing, by which the composite type artificial patina of the basic cupric chloride and the basic copper carbonate is formed.

COPYRIGHT: (C)2003,JPO